

JUNIOR II

THE NEW CLASSIC

100 l/min



TÜV PRODUCT SERVICE ZERTIFIKAT NR. AL 93 12 18738 001



The most compact highly mobile one of our diving compressor range.

Due to its toughness and reliability the JUNIOR has become a global classic.

**JUNIOR II** offers an even more compact design and numerous improvements in details. The patented **TRIPLEX®** filter system guarantees purest breathing air acc. to **DIN EN 12021** (formerly DIN 3188).

Internet: [www.bauer-kompressoren.de](http://www.bauer-kompressoren.de)

## INVEST IN BAUER QUALITY

The new **JUNIOR II** is a product based on more than 50 years of experience and strict BAUER Quality Management according to DIN EN ISO 9001. This is the **uncompromising quality down to the last detail** that has made us the global market leader for breathing air compressor units.



operation at a glance



stainless filling device



easy cartridge exchange

### EASY HANDLING

- Due to symbolic figures it is **child's play to operate** the compressor.
- **Comprehensive documentation** facilitates maintenance work.

### TOUGHNESS

- Durable, **long-life** compressor block
- New fan and pulley protection made of unbreakable, UV-resistant special plastic, which improves cooling air flow for **increased compressor efficiency**.
- filling device: **stainless steel**; filling hose: **kevlar**

### SAFE HANDLING

- Moving parts such as v-belt, pulley and fan have **optimal protection**.
- The **GS-sign** certifies the observation of all relevant safety regulations.

### BAUER WORLDWIDE SERVICE NETWORK

- Profit from the **global service network** and spare parts supply located in more than 50 countries.
- Learn how to do necessary maintenance in BAUER **training courses**.

## TECHNICAL DATA

Type max.330 bar <sup>1)</sup>	Drive	FAD l/min*	min <sup>-1</sup>	Filling- rate min <sup>**</sup>	Engine		filter system TRIPLEX®	Dimensions cm			Weight net kg
					kW	HP		L	W	H	
JUNIOR II - B	4 - stroke petrol <sup>2)</sup>	100	2300	2.0	4.0	5.5	P21	78	34	42	44
JUNIOR II - E	3 phase	100	2300	2.0	2.2	3.0	P21	66	36	42	46
JUNIOR II - W	single phase	100	2300	2.0	2.2	3.0	P21	66	39	42	46

1) available with switch over device 330 / 225 bar or 225 bar/330 bar alternatively

2) with telescopic intake tube and HONDA motor

\* Cylinder filling from 0 to 200 bar

\*\* Filling rate for 1 l cylinder capacity from 0 to 200 bar

### BAUER KOMPRESSOREN GmbH

P.O.BOX 710260 · D-81452 MÜNCHEN  
DRYGALSKI-ALLEE 37 · D-81477 MÜNCHEN  
PHONE 0049 89 78049-0

FAX 0049 89 78049-167

Internet: [www.bauer-kompressoren.de](http://www.bauer-kompressoren.de)

e-mail: [info@bauer-kompressoren.de](mailto:info@bauer-kompressoren.de)

