

Dräger Pac[®] 7000



ST-2507-2005

Small and robust, ergonomic and intuitive, economic and powerful – the Dräger Pac 7000 is tailor-made for personal monitoring at the workplace. This innovative single gas detector is equipped with a wide range of functions and is suitable for many different applications in day-to-day industrial settings. The detector is an impressive instrument, offering a high level of reliability and rapid warning against harmful concentrations of CO, CO₂, Cl₂, HCN, H₂S, NH₃, NO₂, O₂, PH₃, SO₂.



ST-1758-2005

Dräger Pac 7000:
High performance and unlimited use.

Small and robust

With its compact, handy, pocket-sized design, Dräger Pac 7000 is tailor-made for personal monitoring in daily work activities. Dräger Pac 7000 was specially designed as a small and robust instrument to meet work requirements. The impact-resistant housing features a protective rubber coating and is resistant to corrosive chemicals. Dräger Pac 7000 meets the requirements of IP 65. What is more, protection against electromagnetic effects was specially optimized, while a stable and tightly locking crocodile clip made of stainless steel allows the instrument to be fastened securely to the wearer's clothing. To allow for individual preferences, the crocodile clip can be turned and the two alarm lights are positioned diagonally opposite at the corners of the instrument. Easy battery and sensor replacement are key factors to ensure a long instrument life.

Concentration display

The concentration display uses no written text (to avoid language problems), showing all information in the form of large numerals or symbols. In case of an alarm, or at the push of a button, the display can be backlit for better readability. The currently measured concentration is displayed contin-

uously, as are notice and warning functions. In addition, the respective peak concentration, average concentration (TWA value) and short-term exposure limit (STEL) relating to the measurement period can be accessed.

New sensor technology "en miniature"

Dräger Pac 7000 boasts the latest in sensor technology. The small size of the sensor supports the application-oriented design of the instrument. Any gas hazards that may occur are displayed immediately thanks to the very short diffusion paths inside the instrument and the extremely quick electrochemical reaction times achieved by the new sensors. The sensor is positioned inside the housing such as to allow gas to reach it from above and from in front. This positioning minimizes the danger of the gas inlet opening being accidentally covered.

Alarm / warning functions

In conjunction with a vibration alarm, a visual and audible alarm is triggered if the two adjustable alarm thresholds are exceeded (or if oxygen levels fall below the set value). For optimum perception a two-tone alarm is used. Furthermore, Dräger Pac 7000 features an adjustable TWA alarm

and STEL alarm. A warning is likewise given at the end of the battery capacity or in the event of a device error.

Bump test mode

The safety of personnel must always have the first priority. Their safety depends on measurement and warning equipment functioning perfectly, which is why national regulations demand regular testing of equipment function using a known gas concentration. Dräger Pac 7000 is equipped with a bump test mode. When a bump test (function test or challenge test) needs to be performed, a notice icon appears on the screen. The bump test interval can be set by the user.

The result of the bump test is saved in the

The instrument is equipped with an IR interface and can be linked to a PC via the connecting cradle or E-Cal system. Dräger Pac Vision or Dräger CC Vision software installed on the PC enables configuration of all functions, as well as calibration and download of the stored data.

Adjustable operating time

In addition, the instrument allows an individual operating time to be set (in days), e.g. a calibration interval, inspection interval or individual operating time end.

Data logger

Dräger Pac 7000 features a data logger in which all concentrations and events are stored together with their respective dates

DrägerSensors

New XXS sensors react particularly quickly

Large display

Clearly structured, scratch-proof display showing all information at a glance

Robust housing

Impact-resistance and ergonomic design



ST-1758-2005

instrument's memory. Dräger Bump Test Station is available for easy performance of the bump test.

Calibration and configuration

Dräger Pac 7000 features a menu from which the bump test mode, fresh air calibration and span calibration can be selected. Access to fresh air and span calibration can be password-protected.

and times. The intervals at which peak concentrations are saved are variable and can be adjusted by the user. If a one-minute interval is set, the data logger has a capacity of about five days. The stored data can be downloaded via a PC and the installed Dräger Pac Vision or Dräger CC Vision software and edited using, for example, Microsoft® EXCEL® software or Dräger GasVision software.

Dräger Pac 7000 at a glance

- Gas inflow from top and front
- Unlimited instrument life
- Easy sensor replacement
- No-text display (no language problems)
- Continuous concentration display
- Visual alarm
- Audible alarm
- Vibration alarm
- Two adjustable alarm thresholds
- Adjustable TWA alarm
- Adjustable STEL alarm
- Display of peak concentration
- Battery pre- and main alarm
- Adjustable operating time with pre- and main alarm
- Adjustable bump test interval
- Adjustable bump test mode
- Password-protected menu for fresh air and sensitivity calibration
- IR interface
- Individual instrument configuration
- Replaceable battery
- Data logger

For further information, please visit:
www.draeger-safety.com/pac



ORDER INFORMATION

Description	Measuring	Alarms	Alarms	Order-code
		Threshold A 1	Threshold A 2	
Dräger Pac 7000 CO ¹⁾	0 to 1999 ppm	30 ppm	60 ppm	83 18 673
Dräger Pac 7000 CO ²⁾	0 to 1999 ppm	35 ppm	50 ppm	83 18 970
Dräger Pac 7000 CO	0 to 1999 ppm	by customer request		83 18 676
Dräger Pac 7000 H ₂ S ¹⁾	0 to 100 ppm	10 ppm	20 ppm	83 18 674
Dräger Pac 7000 H ₂ S ²⁾	0 to 100 ppm	10 ppm	20 ppm	83 18 971
Dräger Pac 7000 H ₂ S	0 to 100 ppm	by customer request		83 18 677
Dräger Pac 7000 O ₂ ¹⁾	0 to 25 Vol.-%	19 Vol.-%	23 Vol.-%	83 18 675
Dräger Pac 7000 O ₂ ²⁾	0 to 25 Vol.-%	19.5 Vol.-%	23.5 Vol.-%	83 18 972
Dräger Pac 7000 O ₂	0 to 25 Vol.-%	by customer request		83 18 678
Dräger Pac 7000 CO ₂	0 to 5 Vol.-%	0.5 Vol.-%	3 Vol.-%	83 18 975
Dräger Pac 7000 Cl ₂	0 to 20 ppm	0.5 ppm	1 ppm	83 18 978
Dräger Pac 7000 HCN	0 to 50 ppm	10 ppm	20 ppm	83 18 973
Dräger Pac 7000 NH ₃	0 to 300 ppm	50 ppm	100 ppm	83 18 979
Dräger Pac 7000 NO ₂	0 to 50 ppm	5 ppm	10 ppm	83 18 977
Dräger Pac 7000 PH ₃	0 to 20 ppm	0.1 ppm	0.2 ppm	83 18 974
Dräger Pac 7000 SO ₂	0 to 100 ppm	1 ppm	2 ppm	83 18 976

¹⁾ Default configuration Europe

²⁾ Default configuration NAFTA

ACCESSORIES

Connecting Cradle, complete with USB cable and Dräger Pac Vision software	83 18 587
Lithium battery	45 43 808
Dust and water filter	45 43 836
Leather carrying case	45 43 822
Dräger Bump Test Station, complete with test gas cylinder 58 L (gas type by customer request)	83 18 586
E-Cal instrument module for connection of 4 Dräger Pac 1000 to 7000 to a Dräger E-Cal Master Station or to Module Adapter	83 18 589

Dräger Pac 7000:
Reliable in daily use.



Dräger Pac 7000:
High level of wearing comfort.

TECHNICAL DATA

Dimensions (H x W x D)	64 x 84 x 20 (battery compartment: 25) mm (2.5 x 3.3 x 0.8 in., battery compartment: 1 in.)	
Weight	120 g (3.8 oz.)	
Ambient conditions	Temperature ¹⁾	-30 to 50 °C (-20 to 120 °F)
	Pressure	700 to 1300 hPa
	Humidity	10 to 90 % r. h.
Ingress protection	IP 65	
Display	Language-free LCD display, continuous indication of concentration, indication of concentration during alarm, peak concentration, TWA- and STEL-concentration, operating time, notice and warning functions	
Battery life (typical at 25 °C, 24 hours of use per day, 1 minutes alarm per day)	CO, H ₂ S	> 5,500 hours
	O ₂	> 2,700 hours
Acoustic alarm	Two-tone-alarm, typical > 90 dB (A) at a distance of 30 cm	
Data logger	Storage of concentration und events with date and time	
Approvals	CE-Sign (89/336/EEC, 94/9/EC)	
	ATEX	II 1 G EEx ia IIC, T4 I M 1 EEx ia I, T 4
	UL	Class I, II, Div 1, Group A, B, C, D, E, F, G, Temp. Code T4
	cUL	Class I, II, Div 1, Group A, B, C, D, E, F, G, Temp. Code T4
	IECEX	EEx ia IIC, T4

¹⁾ Dräger Pac 7000 CO₂ -20 to 40 °C (-4 to 104 °F)
 Dräger Pac 7000 HCN -20 to 50 °C (-4 to 122 °F)
 Dräger Pac 7000 PH₃ -20 to 50 °C (-4 to 122 °F)



SUBSIDIARIES

AUSTRALIA

Draeger Safety Pacific Pty. Ltd.
 Axxess Corporate Park
 Mt. Waverley. Vic 3149
 Tel +61 3 92 65 50 00
 Fax +61 3 92 65 50 95

CANADA

Draeger Canada Ltd.
 7555 Danbro Crescent
 Mississauga, Ontario L5N 6P9
 Tel +1 905 821 8988
 Fax +1 905 821 2565

P. R. CHINA

Beijing Fortune Draeger
 Safety Equipment Co., Ltd.
 Beijing 101300
 Tel +86 10 80 49 80 00
 Fax +86 10 80 49 80 05

FRANCE

Dräger Safety France S.A.S.
 3c, Route de la Fédération
 67025 Strasbourg Cedex
 Tel +33 388 40 76 76
 Fax +33 388 40 76 67

MEXICO

Draeger Safety S.A. de C.V.
 Av. Peñuelas No. 5
 Querétaro, Qro México
 Tel +52 442 246 1113
 Fax +52 442 246 1114

NETHERLANDS

Dräger Safety Nederland B.V.
 Edisonstraat 53
 2700 AH Zoetermeer
 Tel +31 79 344 46 66
 Fax +31 79 344 47 90

SINGAPORE

Draeger Safety Asia Pte. Ltd.
 67 Ayer Rajah Crescent # 06 03
 139950 Singapore
 Tel +65 68 72 92 88
 Fax +65 67 73 20 33

REP. OF SOUTH AFRICA

Dräger South Africa (Pty) Ltd.
 P.O.Box 68601
 Bryanston 2021
 Tel +27 11 465 99 59
 Fax +27 11 465 69 53

SPAIN

Draeger Safety Hispania S.A.
 Calle Xaudaró 5
 28034 Madrid
 Tel +34 91 728 34 00
 Fax +34 91 729 48 99

UNITED KINGDOM

Draeger Safety UK Ltd.
 Kitty Brewster Industrial Estate
 Blyth, Northumberland NE24 4RG
 Tel +44 1670 352 891
 Fax +44 1670 356 266

USA

Draeger Safety, Inc.
 101 Technology Drive
 Pittsburgh, PA 15275
 Tel +1 412 787 8383
 Fax +1 412 787 2207

Dräger Safety AG & Co. KGaA

Revalstrasse 1
 23560 Luebeck, Germany
 Tel +49 451 882 0
 Fax +49 451 882 2080
www.draeger-safety.com