Dräger CVP 5220 Comfort Vest



The Dräger CVP 5220 comfort vest is a must for any work operation that involves high temperatures.



Dräger CVP 5220 Comfort Vest



Dräger CVP 5220 Comfort Vest open



PCM-element CVP 5220

The Dräger CVP 5220 comfort vest helps to absorb excess body heat and offers comfort for the wearer when working in hightemperature surroundings or performing tasks that are physical enough to cause sweating. It can simply be worn underneath protective clothing such as the TeamMaster pro-ET chemical protective suit.

Its cooling action is derived from 22 PCMelements (Phase Change Material) integrated into the cooling vest, whose primary content is sodium sulphate decahydrate. At temperatures below 22°C, the content of the PCM-elements is in a solid state. At a surface temperature of 28°C, the content of the PCM-elements becomes liquid through absorption of heat energy. At higher ambient temperatures, the raised body temperature of the comfort vest wearer can be reduced by approx. 3-4°C.

Depending on the level of physical work and the ambient temperature, the cooling benefit for the wearer of the vest can last for up to 3 hours.

An ambient temperature of lower than 20°C provokes a phase change and the contents of the PCM elements become solid again within approx. 30 min. - 2 hours.

The CVP 5220 comfort vest can be used in a wide range of applications. It is especially ideal for use underneath gas-tight chemical protective suits such as those from the TeamMaster series, or in industrial applications, in firefighting training, shipping, mining or blast furnace works.

- no need to pre-freeze the cooling elements
- very good logistics, since ready to use straight away
- easy to put on with Velcro fastening
- greater comfort through a multitude of cooling elements
- low weight
- barely combustible

Dräger CVP 5220 Comfort Vest – another quality product from Dräger Safety.



TECHNICAL DATA

Body temperature difference when using the Cooling Vest:	3-4°C, 5.4-7.2°F		
Deployment time:	Approx. 1.5 - 3 hours		
Weight complete, including cooling elements:	Approx. 2.3 kg		
Cooling surface:	Approx. 0.22 m ²		
Material (vest):	polyester		
Material (cooling element):	salt crystal mixture, packed in aluminium moisture barrier bag		
Colour:	inside: black	outside: grey	
PCM elements	large: 20 pieces	small: 2 pieces	
Restoration time of cooling elements:	at +20°C, 68.0°F	approx. 2 hours	
	at +8°C, 46.4°F	approx. 30 minutes	
Storage condition:	horizontal		
Storage temperature:	< 22°C, 71.6°F		

ORDER INFORMATION

Dräger CVP 5220 Comfort Vest, chest size:	84 - 100 cm	-> S / M	incl. 22 PCM elements	R 45 101
Dräger CVP 5220 Comfort Vest, chest size:	100 - 116 cm	-> L / XL	incl. 22 PCM elements	R 45 102
Dräger CVP 5220 Comfort Vest, chest size:	116 - 132 cm	-> XXL / XXXL	incl. 22 PCM elements	R 45 103
Dräger CVP 5220 Comfort Vest, chest size:	132 - 148 cm	-> XXXXL / XXXXXL	incl. 22 PCM elements	R 45 100

Other accessories:

PCM-element, large:	R 45 104
PCM-element, small:	R 45 105
Transportation bag (blue):	R 53 373

г

L

SUBSIDIARIES

AUSTRALIA

Draeger Safety Pacific Pty. Ltd. Mt. Waverley. Vic 3149 Tel +61 3 92 65 50 00 Fax +61 3 92 65 50 95

CANADA

Draeger Canada Ltd. Mississauga, Ontario L5N 6P9 Tel +1 905 821 8988 Fax +1 905 821 2565

P. R. CHINA

Beijing Fortune Draeger Safety Equipment Co., Ltd. Beijing 101300 Tel +86 10 80 49 80 00 Fax +86 10 80 49 80 05

FRANCE

Draeger Industrie S.A.S. 67025 Strasbourg Cedex Tel +33 388 40 76 76 Fax +33 388 40 76 67

MEXICO

Draeger Safety S.A. de C.V. Querétaro, Qro México Tel +52 442 246 1113 Fax +52 442 246 1114

NETHERLANDS

Dräger Safety Nederland B.V. 2700 AH Zoetermeer Tel +31 79 344 46 66 Fax +31 79 344 47 90

SINGAPORE

Draeger Safety Asia Pte. Ltd. 139950 Singapore Tel +65 68 72 92 88 Fax +65 67 73 20 33

REP. OF SOUTH AFRICA

Dräger South Africa (Pty) Ltd. Bryanston 2021 Tel +27 11 465 99 59 Fax +27 11 465 69 53

SPAIN

Draeger Safety Hispania S.A. 28034 Madrid Tel +34 91 358 02 44 Fax +34 91 729 48 99

UNITED KINGDOM

Draeger Safety UK Ltd.
Blyth, Northumberland NE24 4RG
Tel +44 1670 352 891
Fax +44 1670 356 266

USA

Draeger Safety, Inc. Pittsburgh, PA 15275 Tel +1 412 787 8383 Fax +1 412 787 2207

Dräger Safety AG & Co. KGaA Revalstrasse 1 23560 Luebeck, Germany Tel +49 451 882 0 Fax +49 451 882 2080 www.draeger.com